



FUNCTION, MEET FORM.

The new fire-rated door frame from Contact Industries allows architects and contractors to comply with the strictest of fire ratings without compromising aesthetics. Contact's innovative technologies can wrap frames in a virtually unlimited assortment of hardwood and softwood veneers, as well as paint-grade and high pressure laminates, to match doors, casings and interior trim.

The frame's unique composite design incorporates intumescent material directly into the frame itself, offering significant cost savings while maintaining the wall system's ability to achieve the necessary fire rating. Frames are capable of meeting US and UK standards for fire ratings up to 120 minutes, and are available in single- or double-rabbit for single and double openings, as well as communicator frames.



Features and Benefits:

- Patented frame composition; fire-rated up to 120 minutes
- No special fillers or joint compound required to maintain fire rating
- Can be used with positive pressure or neutral pressure tested doors and hardware
- Available in paint grade, high-pressure laminate or wood veneer
- Available with factory applied stains and topcoats, including UV finishing. Versatile finishes allow frames to match entire millwork package.
- Can match virtually any wood veneer species
- Adjustable clip anchorage simplifies installation; no exposed fasteners
- Available as a single-rabbet, double-rabbet, or communicator frame

System Specifications	20-, 45- and 60- Minute positive or Neutral pressure		90- and 120- Minute positive or Neutral pressure	
	MIN	MAX	MIN	MAX
WALL THICKNESS	4 3/4"	None	5"	None
Opening Width, Single Swing	None	Up to 48"	None	Up to 48"
Opening Width, Pairs	None	Up to 84"	None	Up to 84"
Opening Height	None	Up to 96"	None	Up to 96"
Jamb Thickness	7/8"	None	7/8"	None



Contact Industries
 9200 SE Sunnybrook Blvd., Suite 200
 Clackamas, OR 97015
 800-547-1038
 Fax 503-221-1340
www.contactind.com

